# Hangzhou Epsilon Chemical Co.,Ltd.



## **Material Safety Data Sheet (MSDS)**

Version: 2.0

Revised date: Apr. 15, 2013

Print date: Jul. 15, 2013

## Solvent Black 43

1. Supplier: HANGZHOU EPSILON CHEMICAL CO.,LTD.

Phone nr: +86-571-82270817 Fax nr: +86-571-82660715 E-mail: dyestuffs@epsilonpigments.com In case of emergency: Phone nr: +86-571-82270817

2. COMPOSITION AND INFOMRATION ON THE INGREDIENTS: Chemical characterization: Product name: Solvent Black 43

CAS NO: 69458-41-9

## **3. HAZARD IDENTIFICATION:**

Risk Symbol: Risk symbol not required Risk phase: N. A. Recommendations: no Hazardous component

## 4. FIRST AID MEASURES:

Contact with the skin: Flush skin with flowing water immediately Contact with eyes: Immediately flush eyes with plenty of water at least 15 minutes Ingestion: Immediately in due vomiting Inhalation: Remove to fresh air-, if no breathing, give artificial respiration

## **5. FIRE PRECAUTIONS:**

Appropriate extinguishers: Foam CO<sub>2</sub> dry powder Prohibited means of extinguishing: water Risks from products of combustion: N A

## 6. MEASUREES IN THE CASE OF ACCIDENTAL SPILLAGE:

Individual precautions: far away from goods Environmental precautions: clean environment with water Methods of drainage: Remove water with container

#### 7. HANDLING AND STORAGE:

Precautions in handling: keep container tightly closed Storage conditions: keep tightly closed packing, store in cool place Recommended of container: Normal container

## 8. CONTROL OF INDIVIDUAL EXPOSURE AND PROTECTION:

Precautionary measures: Protection of the hands: Rubber gloves Protection of the eyes: Protecting Glasses Respiratory protection: approved respirator

## 9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance at 20 °C: **BLACK POWDER** Odor: Odorless Flash point: N.A Melting point: 250 °C Decomposition point or range: above 300 °C Solubility in water at 80 °C: Insoluble

Hangzhou Epsilon Chemical Co.,Ltd. T.: +86-571-82270817 F.: +86-571-82660715 E: info@epsilonpigments.com W: <u>http://www.epsilonpigments.com</u>

## **10. STABILITY AND REACTIVITY:**

Conditions to be avoided: in wet places Incompatibility with: N.A. Dangerous products of decomposition: NO

#### **11. TOXICOLOGIVAL INFORMATION:**

Acute oral toxicity: LD<sub>50</sub>(Rat): 820**0mg/kg** Coetaneous irritation: N.A Ocular irritation: N.A

#### **12. ECOLOGICAL INFORMATION:**

Ichthyotoxicity LCO : N.A LC<sub>50</sub>(Fish): **1100 mg/L** 

#### **13. DISPOSAL CONSIDERATIONS:**

Product: dispose in accordance with local and state laws Contaminated packaging: not permitted

## **14. TRANSPORT INFORMATION:**

No special information for transport

## **15. REGULATORY INFORMATION:**

88/379/ECC(Classification and labeling)
Classification & labeling: none. The product doesn't need any label
Symbols: none
FDA Status: this product does not have FDA approval as a food additive
USDA Status: this product does not been evaluated by USDA for use in packaging material in direct contact with meat or poultry food product prepared under federal inspection

### **16. OTHER INFORMATION:**

Department issuing data specification sheet; Registration Department Contact: Registration Department Heavy metals: The possible content of soluble heavy metals are micro contaminants are typically below 25ppm for each of the following: Arsenic, Barium, Zinc, Lead, Cadmium, Chromium, Mercury, Nickel

Poly chlorinated biphenyls (PCB): From a theoretical assessment the product does not contains PCB

Inventories:

Australia: the components of the product are included in the AICS Canada: the components of the product are included in the DSL EU: the component of the products are included in the EINECS USA: the components of the product are included in the TSCA

FDA and BGVV Approvals for food packaging: Uncommon with most other pigment the product is not specially approved by FDA and BGVV, but to the best of our knowledge there is no reason for any hesitation as to use the product for food packaging if no migration or peeling.

Aromatic amines: the content is below 500ppm

CONEG: The heavy metal levels referred above for cadmium, lead, mercury and chromium are to be in full complied with the U.S.CONEG permitted maximum concentration of 100ppm in packaging materials.

Hangzhou Epsilon Chemical Co.,Ltd. T.: +86-571-82270817 F.: +86-571-82660715 E: info@epsilonpigments.com W: <u>http://www.epsilonpigments.com</u>